



PRO LIGHT

DOGHER 
® TOOLS

Making Solutions



Work Lights
LED Rechargeables

PRO LIGHT

10h Max. Runtime

2 Lighting Levels

Top Light

Magnetic base and back

Pivot Joint 180°

3.7 V, 2600 mAh Li-ion Battery

Protection Grade IP54 / IK07



Part. N° 1000-003
52,15€

POLLUX

450 lumens
COB LED

- 360° Rigid Hook
- USB-C Socket
- ON/OFF Switch
- Magnet
- Top Light
- Battery Level Indicator
- 199 x 51 x 36 mm



Part.N°: 1000-003



Part. N° 1000-004
54,00€

ADHARA

395nm Wavelength
COB LED

- 360° Rigid Hook
- USB-C Socket
- ON/OFF Switch
- Magnet
- Top Light
- Battery Level Indicator
- 199 x 51 x 36 mm

UV



Max. Runtime 10h

Top Light

Magnetic base and back

Pivot Joint 80°

3.7 V, 2600 mAh Li-ion Battery

Protection Grade IP54 / IK07



Part.N°: 1000-004

8h Max. Runtime

3 Lighting Levels

Top Light

Magnetic base and back

Pivot Joint 180°

3.7 V, 2600 mAh Li-ion Battery

Protection Grade IP65 / IK07



Part. N° 1000-001
53,56€

VEGA

700 lumens
COB LED

- 360° Rigid Hook
- USB-C Socket
- ON/OFF Switch
- Magnet
- Top Light
- Battery Level Indicator
- 268 x 61 x 42 mm



Part.N°: 1000-001



Part. N° 1000-002
52,88€

ALTAIR

400 lumens
COB LED

- 360° Rigid Hook
- USB-C Socket
- ON/OFF Switch
- Magnet
- Top Light
- Battery Level Indicator
- 268 x 61 x 42 mm



Max. Runtime 10h

Top Light

Magnetic base and back

Pivot Joint 180°

3.7 V, 2600 mAh Li-ion Battery

Protection Grade IP54 / IK07



Part.N°: 1000-002



Max. Runtime



Movement Sensor



5 Positions



3.7 V, 1500 mAh Battery LiPo



Protection Grade IP65 / IK07



• High-quality, adjustable, non-slip, ergonomic headband.



Part. N° 1000-030

32,99€



TESTA

400 lumens COB LED

- 0°-60°
- 5 Position Angles
- Contactless ON/OFF movement sensor.
- USB-C Socket
- 47,5 x 78,5 x 42 mm

Part.N°: 1000-030

Max. Runtime



Lighting Levels



Magnetic Base



360° Rotating Base



3.7 V, 1500 mAh Battery LiPo



Protection Grade IP54 / IK07



Part. N° 1000-009

56,31€

COMPACT

300 lumens COB LED

- 360° Rigid Hook
- USB-C Socket
- ON/OFF Switch
- Magnet
- Battery Level Indicator
- 127 x 69 x 33 mm



360°



Part.N°: 1000-009



Max. Runtime



Top Light



Magnetic base and back



3.7 V, 800 mAh Li-ion Battery



Protection Grade IP20 / IK07

Part. N° 1000-015

45,87€

STYLO
150 lumens COB LED

- USB-C Socket
- ON/OFF Switch
- Magnetic Clip
- Top Light
- 167 x 25 x 33 mm



Part.N°: 1000-015



Max. Runtime



Lighting Levels



Top Light



Magnetic base and back



Pivot Joint 180°



3.7 V, 2600 mAh Li-ion Battery



Protection Grade IP44 / IK07



RIGEL

600 lumens COB LED

- Top Light
- Battery Level Indicator
- ON/OFF Switch
- USB-C Socket
- 360° Rigid Hook
- Magnet
- 397 x 66,5 x 46 mm

Part. N° 1000-020
56,40€



Part.N°: 1000-020



SHAULA
280 lumens COB LED

- Pivot Joint 180°
- Battery Level Indicator
- USB-C Socket
- Magnet
- Top Light
- ON/OFF Switch
- 307 x 30 x 17 mm

Part. N° 1000-021
42,78€

Max. Runtime



Lighting Levels



Top Light



Magnetic base and back



Pivot Joint 180°



3.7 V, 750 mAh Li-ion Battery



Protection Grade IP44 / IK07



Part.N°: 1000-021

PRO LIGHT

DOGHER
TOOLS




Lighting

Rechargeable LED Work Lights



COB TECHNOLOGY



Model	Vega	Altair	Polux	Adhara	Compact	Stylo	Rigel	Shaula	Testa
Reference	1000-001	1000-002	1000-003	1000-004	1000-009	1000-015	1000-020	1000-021	1000-030
Luminous Flux	700 lumens	400 lumens	450 lumens	UV 395nm	300 lumens	150 lumens	600 lumens	280 lumens	400 lumens
CRI	80	80	80	80	80	80	80	80/70	80
CCT	6500K	6500K	6500K	6500K	6500K	6500K	6500K	6000K/6500K	6500K
Protection Grade	IP65/IK07	IP54/IK07	IP54/IK07	IP54/IK07	IP54/IK07	IP20/IK07	IP44/IK07	IP44/IK07	IP65/IK07
Lighting Levels	3	1	2	2	2	1	2	2	2
Max. Runtime	8h	10h	10h	10h	8h 30'	4h	9h	4h 30'	8h
Batterie 3.7 V	2600 mAh Li-ion	2600 mAh Li-ion	2600 mAh Li-ion	2600 mAh Li-ion	1500 mAh LiPo	800 mAh Li-ion	2600 mAh Li-ion	750 mAh Li-ion	1500 mAh LiPo
Charging Time	3h 30'	3h 30'	3h 30'	3h 30'	3h	1h 30'	4h	2h	2h 30'
Top Light	150 lumens	120 lumens	100 lumens	100 lumens	NO	80 lumens	100 lumens	150 lumens	NO
	Base & Back	Base & Back	Base & Back	Base & Back	Base	Clip	Base	Base	NO
Pivot Joint	180°	180°	180°	180°	Rotating Base 360°	NO	180°	180°	5 Positions